



# UNLEASH THE POWER OF HEAT SEEKER-OR

THE ULTIMATE HIGH-PERFORMANCE BELT FOR  
EXTREME HEAT & OIL ENVIRONMENTS

Heat Seeker-OR is a custom-engineered belt designed for extreme high-heat and oil-intensive environments, making it ideal for asphalt operations and other demanding applications.

Its proprietary polymer blend provides exceptional durability during extended exposure to heat and oil, far outperforming generic nitrile-based belts.

Heat Seeker-OR is one of the first belts specifically crafted to meet the rigorous demands of live bottom trailers, offering unmatched performance and reliability.







# TECHNICAL SPECIFICATIONS

Specification	Standard	Value
Width		955mm
Total Thickness		11.3mm
Top Cover Thickness		6mm
Bottom Cover Thickness		2mm
Extended Heat Resistance	DIN 22102	220°C
Peak Heat Resistance	DIN 22102	270°C
Min Operating Temperature	DIN 22102	-20°C
Tensile Strength (min)	DIN 22102	15 MPA
Elongation at Break (min)	DIN 22102	450%
Abrasion Loss (max)	DIN 22102	250 mm3
Ozone Resistance	ASTM D1149 - 16	96h 50pphm
Oil Resistance		Excellent



HEAT  
RESISTANCE



OIL  
RESISTANCE



DURABILITY



ANTI-STATIC  
PROPERTIES

Ready to optimise your operations  
with Heat Seeker-OR?

Contact our team today to discuss your needs and see  
how this cutting-edge belt can transform your productivity.

BELT WISE SALES TEAM



Email: [sales@beltwise.com.au](mailto:sales@beltwise.com.au)  
Website: [beltwise.com.au](http://beltwise.com.au)